

Congelatore professionale da Laboratorio -25°C



Ideale per la corretta conservazione a bassa temperatura.

Ottimo isolamento termico su tutte le pareti.

Interno in Acciaio Inox - Esterno verniciato

Ripiani estraibili e regolabili in altezza.

Porta con guarnizioni magnetiche e chiave.

Microinterruttore Apertura ante

Pannello comandi con Sistema di Controllo della Temperatura Digitale con Display 0,1°C

Gestione degli Allarmi.

Sonde di temperatura al Platino PT1000.

Compressore ermetico con Gas Ecologico.

Alimentazione 230V 1f 50Hz

CODICE	GFREEZY Congelatore da Laboratorio	Dim Interne LxPxH mm	Dim.Esterne LxPxH mm	Peso netto kg	Dim.Imballo LxPxH mm	Peso lordo kg
GFREEZ-700XC2	GFREEZY 700L Congelatore da Laboratorio -10-25°C, Ventilato, 4 Ripiani, Digitale, All.AcusticoVisivo, DataLogger, USB	580x670x1500	700x800x1990	150	850x750x2150	162



Professional Laboratory Freezer -25°C



Suitable for low temperature storage.
Excellent thermal insulation on every wall.
Stainless Steel internal chamber.
Galvanized Steel exterior, PVC coated.
Extractable and height adjustable shelves.
Door with magnetic gaskets and lock with key.
Microswitch at door opening.
Control panel with digital temperature control system and 0,1°C display.
Alarm control system.
Platinum PT1000 temperature probes.

Hermetic compressor with ecofriendly gas.

Power supply 230V 1f 50Hz

CODE	GFREEZY Laboratory Freezer	Interior Dim. WxDxH mm	Exterior Dim. WxDxH mm	Net Weight kg	Packaging Dim. WxDxH mm	Gross Weight kg
GFREEZ-700XC2	GFREEZY 700L Laboratory Freezer -10-25°C, Ventilated, 4 Shelves, Digital, Visual Acoustic Alarm, DataLogger, USB	580x670x1500	700x800x1990	150	850x750x2150	162

